

Cut-off Saw



- Easily cuts concrete, stone, or steel when equipped with the appropriate blade (blade not included).
- Comes complete with a threaded water hose port.
- 24 in. (610 mm) whip hoses.
- Auxiliary handle.
- Rugged gear motor.
- Adjustable debris guard.
- Optional three-wheel cart (137125/41055) available.

Cat. No.	UPC No.	Description
H6245	42252	Cut-off Saw - Open-Center
F020196K	41778	Body 1/2 in. NPTF
F020197K	41779	Nose Piece 1/2 in. NPTF
F019329	42993	14 in. (356 mm) Metal Blade
F019330	42994	14 in. (356 mm) Concrete Blade

SPECIFICATIONS

System: Open-Center  
 Cutting Capacity: 5.25 in. (133 mm) with 14 in. (356 mm) blade  
 Blade Diameter: 14 in. (356 mm) max.  
 Arbor Shaft Diameter: 1 in. (25 mm)  
 Weight: 21 lb. (9.5 kg)  
 Length: 26.5 in. (673 mm); Width: 5.5 in. (140 mm)  
 Flow Range: 5 - 8 gpm (18.9 - 30 lpm)  
 Operating Pressure: 1,000 - 2,000 psi (69 - 140 bar)  
 Blade Speed: 4,100 rpm at 8 gpm (30 lpm)  
 Pressure and Return Port Thread.: 3/8 NPTF (Tool), 1/2 NPTF (Hose End)

Cut-off Saw Cart



- Optional three-wheel cart for use with H6245/42252. (Saw not included with cart).
- For precision depth control and straight line cutting from a standing position.
- Single clamp mounting feature for quick mounting or removal of the saw from the cart.
- Removable handle - allows cuts to be made within 3 in. (76 mm) of an obstruction.
- Depth control crank handle and locking nut.

Cat. No.	UPC No.	Description
137125	41055	Cut-off Saw Cart

SPECIFICATIONS

Length: 27-1/2 in. (700 mm)  
 Width Across Handle: 19-1/2 in. (495 mm)  
 Width Across Wheels: 14-1/2 in. (368 mm)  
 Height: 36-3/4 in. (933 mm)  
 Weight: 59 lb. (26.8 kg)  
 Wheel Diameter: 6 in. (155 mm)