

Features:

- Real-Time Continuous Gain Adjustment™ and Manual Gain – A First in Locator Technology
- Superior Sensor Technology – Improved Accuracy and Productivity
- Lighted Display on all Models – Low light operations without a flashlight
- Distant Sensitive Left/Right Guidance™
- Multi-Frequency- 3 Active & 2 Passive
- Current Measurement
- Push – Button Depth
- Automatic “Best” Frequency Select
- “ALL” Frequency Transmission



Standard Equipment:

Transmitter, Receiver with Display Backlighting, Conductive Attachment, Ground Rod, Carrying Case, and Operation Manual.

Accessories:

Metroclamps – 4290 (2”), 4490 (4”), 4890 (8”), Vehicle Mount Changer (P/N 400B252) for Rechargeable Transmitter Batteries, Telephone style clamps on Conductive Attachment (P/N 400B246), Headphones (P/N 183048), Sondes.

9800 XT Receiver Technical Data

	9860 XT	9890 XT
Receiving Frequencies:	Active - 9.8kHz and 82 kHz Passive - 50/60 Hz and 14-22 kHz	982 Hz, 9.8 kHz and 82kHz 50/60 Hz and 14-22 kHz
Depth Readout Accuracy:	± 5% + 2" under normal conditions	± 5% + 2" under normal conditions
Distance Sensitive Left/Right Guidance™	Included	Included
Real-Time Continuous Gain Adjustment™	Included	Included
Manual Gain/Peak Mode	Included	Included
Current Measurement	Included	Included
Backlighting	Included	Included
Battery Type	Six AA Cells	Six AA Cells
Battery Life:	30 hours continuous use	30 hours continuous use
Battery Check:	Continuous Automatic	Continuous Automatic
Operation Temperature:	-4° to + 122° F (-20° to + 50° C)	-4° to + 122° F (-20° to + 50° C)
Dimensions:	27" L x 7" W x 9" H (68.6 cm x 17.8 cm x 22.9 cm)	27" L x 7" W x 9" H (68.6 cm x 17.8 cm x 22.9 cm)
Weight:	5.24 lbs (2.35 kg)	5.24 lbs (2.35 kg)

9800 XT Transmitter Technical Data

	9860 XT	9890 XT
Output Frequencies:	Active - 9.8 kHz and 82 kHz Optional 4.8 Hz Fault Locating	982 Hz, 9.8 kHz and 82 kHz Optional 4.8 Hz Fault Locating
Simultaneous Frequency Output:	9.8 kHz and 82 kHz	982 Hz, 9.8 kHz and 82kHz
Automatic “best” Frequency Selection	Included	Included
Ohm Meter:	0-2kOhm	0-2kOhm
Nominal Output Power Conductive Mode:	3 watts	3 watts
Power Settings:	Low, Medium, High	Low, Medium, High
Battery Type:	Ten D Cells Optional Rechargeable NiCd	Ten D Cells Optional Rechargeable NiCd
Battery Life:	Alkaline – 28 to 70 hours NiCd – 9 to 22 hours Continuous use depending on power and frequency selection	Alkaline – 28 to 70 hours NiCd – 9 to 22 hours Continuous use depending on power and frequency selection
Battery Check:	Automatic at start-up	Automatic at start-up
Operation Temperature:	-4° to + 122° F (-20° to + 50° C)	-4° to + 122° F (-20° to + 50° C)
Dimensions:	14.25" L x 9.25" W x 5.25" H (36.2 cm x 23.5 cm x 13.3 cm)	14.25" L x 9.25" W x 5.25" H (36.2 cm x 23.5 cm x 13.3 cm)
Weight:	8.9 lbs (4 kg)	8.9 lbs (4 kg)

Service Center, Ordering, and Technical Support Information

Corporate Headquarters

Western United States Service Center
488 Tasman Dr., Sunnyvale, CA 94089
Sales Tel: 1.800.446.3392 (U.S./Canada)
Service Tel: 1.800.638.7682
Tel: +1.408.734.1400 (International)
Fax: +1.408.734.1415
www.metrotech.com;
sales@metrotech.com

Metrotech Eastern United States Service Center

1824 Murfreesboro Rd., #104
Nashville, TN 37217
Tel: 1.800.624.6210 (U.S./Canada)
Tel: +615.366.7323 (International)
Fax: +1.615.360.9855
nashville@metrotech.com

Metrotech European Service Center

Seba Dynatronic GmbH
Dr.-Herbert -Iann-Str. 6, D-96148
Baunach, Germany
Tel: +49.9544.680
Fax: +49.9544.2273
www.sebadyn.de; service@sebadyn.de

Warranty – One year provided on parts and labor
Specifications subject to change without notice. Copyright 2003

ISO 9001 Certified

