



ONE TO SIX GAS PORTABLE MONITOR

Gas Detection For Life

EAGLE™ Model



Features

- Simultaneous detection of up to 6 different gases
- Over 250 gas monitoring configurations
- Widest range of gas sensors available
- PPM / LEL hydrocarbon detection
- Powerful long-life pump with 125' range
- Low flow pump shut off and alarm
- Methane elimination switch for environmental use
- Security "Adjustment Lockout Switch"
- Up to 30 hours of continuous operation
- IR Sensors available for CO₂, % LEL CH₄, and 0-100% volume CH₄
- Transformer testing version available
- Alkaline or Ni-Cad capability
- Ergonomic RFI/EMI/Chemical resistant case
- Datalogging option
- Autocalibration
- Intrinsically safe design, CSA/NRTL & UL Classified (most versions)

RKI is proud to produce the most versatile portable gas detector on the market. The EAGLE is a powerful instrument that does more than offer standard confined space protection. The EAGLE also provides detection combinations never before offered in a portable gas monitor featuring the industry's widest selection of high quality, long life and field proven sensors.

The EAGLE's ergonomic design offers easy access to controls such as autocalibration, alarm silence, demand zero, peak hold and a wide variety of other features. Each channel has 2 alarm levels plus TWA and STEL alarms for toxic channels. Alarm levels are adjustable and can be latching or self resetting.

Standard features on the EAGLE are not available on other competitive units. These features include PPM/LEL hydrocarbon detection and a methane elimination switch for environmental applications. For quick response and recovery, the EAGLE has a strong internal pump which can draw samples from over 125 feet. The EAGLE will continuously operate for over 30 hours on alkaline batteries or 18 hours on Ni-Cads. Many accessories such as long hoses, special probes, data-logging, continuous operation adapters, remote alarms and strobes, dilution fittings, internal hydrophobic filter, etc, are available to help satisfy almost any application. Rugged, weatherproof, easy to operate and maintain, the EAGLE is the industry's answer to portable gas detection.

RKI Instruments, Inc. • 1855 Whipple Rd. Hayward, CA 94544 • Phone (800) 754-5165 • (510) 441-5656 • Fax (510) 441-5650

World Leader In Gas Detection & Sensor Technology
www.rkiinstruments.com

Enclosure	Weatherproof, chemical resistant, RFI/EMI coated high impact polycarbonate-polyester blend. Can be set in rain or into 2.5" of water without damage. Ergonomically balanced with rugged top mounted handle.
Dimensions	10.5" L x 5.9" W 7" H
Weight	5 lbs
Detection Principle	Catalytic combustion, electrochemical cell, galvanic cell, and infrared.
Sensor Life	2 years under normal conditions.
Sampling Method	Powerful, long-life pump (over 6,000 hours) can draw samples over 125 feet. Flow rate approximately 2.0 SCFH.
Display	4 x 20 LCD readout with backlighting. Viewed through window in case top. Displays readings & status of all channels simultaneously.
Alarms	2 alarms per channel plus TWA and STEL alarms. Fully adjustable for levels, latching or self reset and silenceable.
Alarm Method	Buzzer 85dB at 30 cm, dual high intensity LED's, and flashing display.
Controls	6 external push buttons for operation, demand zero, and autocalibration. Buttons also access LEL/ppm, alarm silence, peak hold, TWA / STEL values, battery status and many other features.
Continuous Operating Hours	30 hours minimum using alkaline batteries, or 18 hours using Ni-Cads.
Power Source	Size D batteries, 4 alkaline or Ni-Cad. Charger has alkaline recognition to prevent battery damage if charging is attempted with alkalines.
Operating Temp. & Humidity	-10°C to 40°C (14°F to 104°F), 0 to 95% RH, non-condensing.
Indication Accuracy	Maximum variance +/- 5% of full scale.
Response Time	30 seconds to 90% (for most gases).
Safety Design	Intrinsically Safe, Class I, Division 1, Groups A, B, C and D. CSA / NRTL & UL Classified (most versions).
Standard Accessories	Shoulder strap, alkaline batteries, hydrophobic probe and 5 foot hose (for special toxic gas versions, shorter teflon hose used without probe).
Optional Accessories	<ul style="list-style-type: none"> • Datalogging of up to 4 gases (No datalogging possible on 5 or 6 gas versions or versions with more than 2 toxic sensors). • Remote alarm • Dilution fitting (50/50) • Ni-Cad batteries • Battery charger, 115 VAC, 220 VAC, or 12 VDC • Continuous Operation Adapter, 115 VAC or 12 VDC • Extra loud buzzer • Extension Probes • Internal Hydrophobic Filter (strongly recommended)
Warranty	One year material and workmanship.

Gases & Detectable Ranges

Standard Confined Space Gases	
Hydrocarbons (CH ₄ , std)	0 - 100% LEL 0 - 50,000 ppm
Oxygen (O ₂)	0 - 40% Vol.
Carbon Monoxide (CO)	0 - 500 ppm
Hydrogen Sulfide (H ₂ S)	0 - 100 ppm
Super Toxics and Other Gases	
Ammonia (NH ₃)	0 - 75 ppm
Arsine (AsH ₃)	0 - 1 ppm 0 - 200 ppb
Carbon Dioxide (CO ₂) (I R Sensor)	0 - 5,000 ppm 0 - 10,000 ppm 0 - 5% Vol. 0 - 20% Vol. 0 - 50% Vol.
Chlorine (Cl ₂)	0 - 3 ppm
Fluorine (F ₂)	0 - 5 ppm
Hydrogen Fluoride (HF)	0 - 9 ppm
Hydrogen Chloride (HCl)	0 - 5 ppm
Hydrogen Cyanide (HCN)	0 - 30 ppm
Methane (CH ₄) (IR Sensor)	0 - 100% LEL 0 - 100% Vol.
Nitrogen Dioxide (NO ₂)	0 - 15 ppm
Nitric Oxide (NO)	0 - 100 ppm
Ozone (O ₃)	0 - 1 ppm
Phosphine (PH ₃)	0 - 1 ppm
Silane (SiH ₄)	0 - 15 ppm
Sulfur Dioxide (SO ₂)	0 - 30 ppm

The EAGLE can be provided with up to 6 gas sensors (2 Toxics maximum from "super toxics" list). Please specify gas combination when ordering.

Special Features

- Low Flow alarm shuts pump off to avoid damage to instrument.
- Hydrophobic filter disc in probe.
- Internal dust filter (or optional internal hydrophobic filter).
- Quick autocalibration using 4 in 1 calibration gas standard.
- Single gas calibration capability.
- Methane elimination switch for environmental applications.
- "Adjustment Lockout Switch" for added security.
- Confirmation beep (silenceable).
- Backlight, automatic for alarms and by demand with adjustable time.
- Meets EPA Method 21 protocol for fugitive emissions testing.

RKI Instruments, Inc.



1855 Whipple Road
Hayward, CA 94544

Toll Free: (800) 754-5165
Phone: (510) 441-5656
Fax: (510) 441-5650

mail4rki@rkiinstruments.com
www.rkiinstruments.com

Authorized Distributor: